IGARSS '93

FIRST RESULTS FROM SIR-C CALIBRATION

A. Freeman, J. Ciuz, B. Chapman, M. Alves, M. Azcem and S. Shaffer

Jet Propulsion Laboratory 4800 Oak Grove 1)1 ive 1'madma.CA91109

The SIR-C/X-SAR imaging radar is scheduled for launch in April 1994. This multi-frequency radar has fully polarimetric capability at L- and C-band, and a single polarization at X-band (X-SAR). Calibration of polarimetric L- and C-band data for all the different modes S1 R-C offers is an especially complicated problem. The solution involves extensive analysis of preflight test data to come up with a model of the system, analysis of in-flight test data to determine the actual antenna pattern and gains of the system during operation, and analysis of data from overten calibration sites distributed around the Sit{-C/X-SAH orbit track.}

The SIR-C mission will be the first time a multi-frequency polarimetric imaging radar employing phased array antenna has been flown in space. The effort put into the calibration of SIR-C data products has bet.11 considerable and is also unique in that [his is the first time anyone has attempted to calibrate a space.hoIIIc radar of this complexity.

First results from the calibration analysis of SIR-C data will be presented at the conference.

This work was performed by the Jet Propulsion Laboratory, California Institute of Technology, undercontract from the National Aeronautics and Space Administration.